

FIBER ACCESSORIES

FIBER TERMINATION BOX - DIN BAR



Description

ORCA® fiber access termination box is able to hold up to 12 subscribers. Is it used as a termination point for the feeder cable to connect with drop cable in FTTx network system. It integrates fiber splicing, splitting, distribution, storage and cable connection in one solid protection box.

Feature:

- Iron 10/10 coating realized - grey colour
- Size 142 x 126 x 40 mm
- 12 port SCdx footprint for SC duplex and LC quad or 8 SCsx for SC simplex or LC duplex adapters
- Water-proof design with IP-54 Protection level
- Integrated with splice cassette and cable management rods
- Manage fibers in a reasonable fiber radius condition
- Easy to maintain and extend the capacity
- Fiber bend radius control more than 40mm
- Suitable for the fusion splice or mechanical splice
- Efficient cable management
- 4 ports cable entrance for drop cable, 2 linear or 2 angled
- Integrated splice tray - no optical adapters included
- Unloaded version with caps to cover empty hole and screws to fix optical adapters



Ordering Information code:

OC-FPP-171100-06U-DIN	ORCA - Terminal optic Box - DIN type - 6 SC DPX port, grey colour, unloaded, with 6 pcs black cover and 12 pcs fixing screw, no adapters.
OC-FPP-171100-08U-DIN	ORCA - Terminal optic Box - DIN type - 8 SC SPX port, grey colour, unloaded, with 8 pcs black cover and 16 pcs fixing screw, no adapters.

Specifications subject to change without prior notice - For more details please visit www.orca.it