

## ORCA - POE Switch Managed 24 porte Fast 10/100M + 2 porte Giga Ethernet Uplink




### 1 Introduction

This item is a 24-port managed PoE Ethernet switch, which provides 24\*100Mbps downlink PoE Ethernet ports, supports IEEE802.3 af/at and 2\*1000Mbps uplink Ethernet ports. It supports Layer 2 network management and PoE management based on web and provides high-speed data forwarding. It is widely used in security surveillance, network engineering projects and so on.

### 2 Feature


- 24 ports managed PoE Ethernet switch provides 24\*10/100Mbps downlink PoE Ethernet ports and 2\*10/100/1000Mbps uplink Ethernet ports ;
- Provide web-based layer 2 network management and PoE management with simple operation process;
- Support high-speed data forwarding, perfectly designed for large flow of video data forwarding in security surveillance;
- Support one-key recovery of IP address & user password;
- Excellent circuit isolation protection, lightning protection up to 6 KV;
- Quick fixing, easily operation and convenient for wall/ desk/ rack installation.

## 3 Application




## 4 Board Diagram

### Front panel



### Back panel



## 5 Specification

Item		Description
Products	Products	24 Ports PoE Ethernet Switch
Power	Power Supply	Mains on load
	Voltage Range	AC 100~240V
	Consumption	420W
Network Connector	Ethernet Port	1 ~24 Ports: 10/100Mbps Ethernet port, adaptive control UPLINK Ethernet port: 10/ 100/ 1000Mbps Ethernet port
	Transmission Distance	1 ~ 24 ports: Recommended 100m; Uplink 1000Mbps Ethernet port: 100m
	PoE Protocol	IEEE802. 3af, IEEE802. 3at
	PoE Power Supply	End-span
	PoE Power Consumption	Each Port ≤30W, Total ≤370W
Network Switch	Network Standard	IEEE802. 3 10BASE- T, IEEE802. 3u 100BASE TX, IEEE802. 3ab 1000BASE- T
	Switch Capacity	8.8Gbps
Management	Management	Management L2
Protection	ESD	Level 3, Per: IEC61000- 4- 2
	Communication Port Lighting Protection	6KV, Per: IEC61000- 4- 5
Environmental	Working Temperature	-10℃ ~55℃
	Storage Temperature	-40℃ ~85℃
	Humidity (non-condensing)	0~95%
Mechanical	Dimension (L xW xH)	442mmx224mmx44.5mm
	Material	Sheet metal
	Color	Black
	Weight	2.79kg

### Ordering Guide

**OC-481212-24** ORCA - POE Switch Managed 24 porte Fast 10/100M + 2 porte Giga Ethernet Uplink

*Features maybe changed without prior notice  
www.orcasystem.com*