

RACK ACCESSORIES - PDU

# PDU 19" 6 SLOT MULTISTANDARD PROTECTED LIGHT SWITCH



## Description

ORCA PDU ready for LAN node, building distribution, supply for server, personal computer, printer, active devices, fan, power factor correction electric loads without cue.

### Construction and characteristics:

- Solid structure in Polycarbonate profile, 1U rack - IP20
- BLACK RAL 9005
- Fixing bracket for 19" standard
- 3 mt power cord, H05VV-F3Gx1,5mmq
- Shuko plug S31 - 90°
- Protected alveoli
- Storage and transport Temperature range. -40 / 70°C
- Operating Temperature range. -20 / 70°C
- 230Vac - 16A - 3500W - 50/60Hz

- Prepared for orizzontal or vertical assembly
- 8 multi standard socket (shuko + IT 10/16A) - 45° angled
- Light switch protected from accidental operation

### Standard Compliace and Approvals:

- |                                |  |
|--------------------------------|--|
| IEC 297-1 (drilling step)      | EN 60529 e CEI 70-1 (degree of protection) |
| IEC 297-2 (rack and structure) | CEI EN 50310 (ground test)                 |
| DIN 41494 (rack 19 ")          | CEI 23-50 (connection test)                |
| CEI 20-20/5 (power cord)       |  |

### Ordering Information code:

OC-PWR-485000-06    ORCA - PDU 19" 16A - 6 SLOT multistandard, protected light switch

Specifications subject to change without prior notice - For more details please visit [www.orca.it](http://www.orca.it)