



FLOOR STANDING SERVER RACK 600x1000x42U

Description

The Orca System floor and wall cabinets are designed and manufactured in compliance with quality and safety standards, optimal solutions for the management and organization of structured cabling.

Orca System offers a range of wall racks with relative accessories. Rack cabinets are distinguished by their exceptional robustness, which, combined with affordability and simplicity of assembly / disassembly, place them at the top of their category.

General Feature:

Physical	Realized in 13,5/10 Steel painted.
	Surface finish BLACK RAL 9011.
	Load-bearing frame
Doors	Static load capacity 800Kg.
	IP20 protection degree in according to EN 60529, IK10.
	Front, single door, perforated 75%
	Rear, vertical double door, perforated 75%
	Reversible, with quick release hinges system.
Roof and floor	With foldaway handle, 2 key supplied.
	Opening 180°
	Roof with predisposition for mounting 2-3-4 fans ventilation unit.
	Passive ventilation slots for the recirculation of hot air.
Other	Pre-punched space for cable inlet.
	Ground kit
	Levelling feet 18mm
	Side panels removable with quick release system, ¼ turn lock
	Front and rear 19 " in 20/10 galvanized steel side uprights adjustable in depth, pitch 46mm with intermediate pitches of 15,875mm
Optional	Weight unload 130Kg
	Finishing plinth H100mm with removable panels
	Wheels and wheels with brake

U	W(mm) Overall/Useful	D(mm) Overall/Useful	H(mm) Overall/Useful
		600x1000x42U	
42	596 / 529	996 / 748	1957 / 1861

Specifications subject to change without prior notice - For more details please visit www.orca.it



Ordering Information code:

600x1000x42U

OC-RAC-572600-42N

ORCA - Floor Standing Server Rack 600X1000X42U, front door, rear double door, perforated 75%; side panels removable, dual side uprights and vertical cable management, disassemblable, feet, load capacity 500Kg, Black